



# data sheet

## MBL3 SPRAY

### Product Information

The unique deep penetrating solvent carries **MBL 3 Spray's** lubricating and plating action into the most rigid areas. Ideal for rusted nuts and bolts, hinges, exposed roller bearings, exhaust manifold and flange bolts, cables and general lubrication.

This quality product enjoys the same micro-metallic particle features as our **MBL 8** and **MBL Grease** the main difference being that it contains a penetrating solvent and is of a much lighter consistency. The **MBL 3 Spray** is a multistage penetrating lubricating spray.

### MBL 3 SPRAY HAS 3 DISTINCT FUNCTIONS;

**1. Penetrates** - Upon spraying the area to be treated, the penetrating solvent starts to work its way into the components. This may be rusted nuts and bolts, door hinges, exposed roller bearings, exhaust manifolds and exhaust flange bolts or any surface that requires freeing and lubrication. As the solvent starts to penetrate it also carries with it the micfilic particles.

**2. Luricates** - As the solvent continues to penetrate and then evaporate, it leaves the lubricating micro-metallic particles. The hotter the area being treated, the quicker the evaporation of solvent. This can be noticed by the smoke coming off the treated surface (as noticed when the spray is demonstrated on the Friction Brake Test Machine). However, if the area is not subjected to heat (such as door hinges), there will be no smoke or initial evaporation.

**3. Plates** - As the lubricating surfaces are worked, the micro-metallic particles plate the scratches and score marks, gradually filling in the worn areas, providing long lasting lubrication of the surface as well as leaving residual lubrication.

Every home, workshop, commercial and industrial business, handyman, boat owner, etc., should have this product on hand for all lubricating and penetrating needs. An absolute asset to your range of sales products, providing many benefits to all types of consumers.

**MBL3 Spray is NOT to be used as a dewatering fluid. By that, we mean it is not to be used to spray your distributor and spark plugs should they become covered in water. It is a lubricating, penetrating spray, not a dewatering fluid.**

### Composition

**MBL 3 Spray** contains elemental micro-metallic particles, a base mineral oil and a high boiling point hydrocarbon penetrating solvent.

### Specification

Base carrier .....oilEP 90  
 Micro-metallic particles .....1-10 Microns  
 Hydrocarbon Solvent - Boiling Point .....Above 150°C(300°F)  
 Appearance.....Grey Brown  
 Odour .....Metallic Petroleum

### Handling

**MBL 3 Spray** contains petroleum oil, hydrocarbon solvent and micro-metallic particles. **Do NOT store near heat, sparks or flame.** Wash with soap and water after skin contact with product. **This**



**product is flammable. KEEP OUT OF REACH OF CHILDREN** A Material Safety Data Sheet is available from Home Office.

### Warning

Do NOT take internally. **Harmful or Fatal if swallowed.** Contains Micro-metallic particles and hydrocarbons. If swallowed contact a doctor immediately. Wash hands after use.

### Medical Advise

Contains petroleum oil, and micro-metallic particles. **If swallowed, do not induce vomiting.** Call physician immediately.

### Avialability

250mL and 4Litre containers.



INDEPENDENT DISTRIBUTOR

**PRO-MA Systems (Aust) Pty. Ltd.** 10 Kingston Drive, Gaven, Gold Coast, Qld. 4211 Australia • Tel (07) 5573 8111 • Fax (07) 5573 8122 • Toll Free 1 800 800 802  
 Email: info@pro-masystems.com.au

**PRO-MA Systems (New Zealand) Ltd.** Unit A, 27B Cain Road, Penrose, Auckland, 1006 New Zealand •Tel. (09) 526 5318 • Fax (09) 526 5319  
 Email: info@pro-masystems.co.nz

**PRO-MA Systems (Papua New Guinea) Ltd.** TNT Complex, Jackson Airport Port Moresby, P.N.G. • Tel (675) 323 0967 • Fax (675) 323 6725  
 Email: info@pro-masystems.com.pg

**Web Site: www.pro-masystems.com**